

### NeoTek - 30 Series - Corded Electric - Transducer Control - Pistol (0.9-26 Nm)

Ergonomic grip and light weight reduces operator fatigue to increase productivity.



- 1 Million Cycles Maintenance Free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
30EPN05BD2	0.9	4.7	0.66	3.47	4275	2.05	0.93	7.76	0.64	1/4" SQ.
30EPN05BDQ	0.9	4.7	0.66	3.47	4275	2.01	0.91	8.27	0.64	1/4" QC
30EPN12EAQ	3.9	11.6	2.88	8.56	1650	2.20	1.00	9.02	0.64	1/4" QC
30EPN12FA3	3.9	11.6	2.88	8.56	1650	2.16	0.98	8.43	0.64	3/8" SQ.
30EPN19FB3	3.9	19.0	2.88	14.01	1000	2.20	1.00	8.43	0.64	3/8" SQ.
30EPN26FB3	5.1	26.0	3.76	19.18	750	2.20	1.00	8.43	0.64	3/8" SQ.

### NeoTek - 50 Series - Corded Electric - Transducer Control - Pistol (5.6-123 Nm)

Ergonomic grip and spline mount ideal for applications up to 123 Nm.



- 1 Million Cycles Maintenance Free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
50EPN28FD3	5.6	28.0	4.13	20.65	2125	3.48	1.58	10.08	0.64	3/8" SQ.
50EPN43GD3	9.0	43.0	6.64	31.72	1375	3.64	1.65	10.24	0.74	3/8" SQ.
50EPN65HD4	14.0	66.0	10.33	48.68	900	4.72	2.14	11.34	0.87	1/2" SQ.
50EPN85JD4	17.0	84.0	12.54	61.96	670	4.89	2.22	11.89	0.87	1/2" SQ.
50EPN125KD4	25.0	123.0	18.44	90.72	455	5.78	2.62	12.32	1.10	1/2" SQ.