

15LF Series - Inline Drill

0.4hp / 0.30kW

600-28500rpm



- Supplied with Jacobs® Keyed Chuck or Threaded Termination for Keyless Chuck/Collet
- Rear Exhaust
- Lock off safety lever standard

MODEL	TERMINATION	SPEED	WEIGHT	LENGTH
		R/MIN	LB	IN
15LF087-38	1/4" CHUCK	600	1.98	8.6
15LF087-40	3/8" - 24 E	600	1.98	8.6
15LF086-38	1/4" CHUCK	750	1.32	8.0
15LF085-38	1/4" CHUCK	1000	1.32	8.0
15LF085-40	3/8" - 24 E	1000	1.32	8.0
15LF084-38	1/4" CHUCK	2400	1.32	8.0
15LF083-38	1/4" CHUCK	3300	1.32	8.0
15LF083-40	3/8" - 24 E	3300	1.32	8.0
15LF082-38	1/4" CHUCK	4000	1.32	8.0
15LF082-40	3/8" - 24 E	4000	1.32	7.3
15LF081-38	1/4" CHUCK	5300	1.32	8.0
15LF081-40	3/8" - 24 E	5300	1.32	8.0
15LF080-38	1/4" CHUCK	28500	0.9	0.63

All tools performance rated @ 90psi / 620 kPa air pressure.  
Air inlet size: 1/4in  
Minimum Hose I.D.: 1/4in / 6.4mm  
Standard Equipment: Jacobs geared chuck, chuck key  
Drill diameter capacity matches chuck size.