

NeoTek - 70 Series - Corded Electric - Transducer Control - Right Angle (39-350 Nm)



Durability and unsurpassed RPM for high torque applications up to 350 Nm.

- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
70EAN155NA6	39.0	156.0	28.76	115.06	740	14.33	6.50	25.07	1.16	3/4" SQ.
70EAN205NA6	52.0	205.0	38.35	151.20	555	14.33	6.50	25.07	1.16	3/4" SQ.
70EAN240PA6	60.0	239.0	44.25	176.28	480	15.43	7.00	25.78	1.49	3/4" SQ.
70EAN350PA6	88.0	350.0	64.91	258.15	325	15.43	7.00	25.78	1.49	3/4" SQ.

Note: 70 Series Tools require a 220/230 power supply to the controller

NeoTek - 30 Series - Corded Electric - Transducer Control - Inline (0.9-26 Nm)



High speed and accuracy for applications up to 26 Nm. Mounts easily with machined splines and locknut.

- 1 Million Cycles Maintenance Free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
30ESN05BD2	0.9	4.7	0.66	3.47	4275	2.12	0.96	13.27	0.64	1/4" SQ.
30ESN05BDQ	0.9	4.7	0.66	3.47	4275	2.12	0.96	13.46	0.64	1/4" QC
30ESN12EAQ	3.9	11.6	2.88	8.56	1650	2.34	1.06	14.21	0.64	1/4" QC
30ESN12FA3	3.9	11.6	2.88	8.56	1650	2.34	1.06	14.05	0.64	3/8" SQ.
30ESN19FB3	3.9	19.0	2.88	14.01	1000	2.34	1.06	14.05	0.64	3/8" SQ.
30ESN26FC3	5.1	26.0	3.76	19.18	750	2.34	1.06	14.05	0.64	3/8" SQ.

NeoTek - 50 Series - Corded Electric - Transducer Control - Inline (5.6-84 Nm)

High speed and accuracy for applications up to 123 Nm. Mounts easily with machined splines and locknut.



- 1 Million Cycles Maintenance Free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT		LENGTH IN	SIDE TO CENTER IN	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB		LB	KG			
50ESN28FD3	5.6	28.0	4.13	20.65	2125	2.98	1.35	15.70	0.64	3/8" SQ.
50ESN43GD3	9.0	43.0	6.64	31.72	1375	3.64	1.65	15.86	0.74	3/8" SQ.
50ESN65HD4	14.0	66.0	10.33	48.68	900	4.19	1.90	17.12	0.86	1/2" SQ.
50ESN85JD4	17.0	84.0	12.54	61.96	670	4.41	2.00	17.67	0.86	1/2" SQ.
50ESN125KD4	25.0	123.0	18.44	90.72	455	5.29	2.40	18.11	1.10	1/2" SQ.

NeoTek - 70 Series - Corded Electric - Transducer Control - Inline (23-850 Nm)

Durability and unsurpassed RPM for high torque applications up to 850 Nm.



- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT		LENGTH IN	SIDE TO CENTER IN	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB		LB	KG			
70ESN95ND6	23.0	93.0	16.96	68.59	1325	11.46	5.20	22.28	1.30	3/4" SQ.
70ESN130ND6	31.0	124.0	22.86	91.46	1000	11.46	5.20	22.28	1.30	3/4" SQ.
70ESN185ND6	46.0	184.0	33.9	135.7	680	11.46	5.20	22.28	1.30	3/4" SQ.
70ESN245ND6	61	245.0	45.73	180.70	510	11.46	5.20	22.28	1.30	3/4" SQ.
70ESN355SD8	89.0	354.0	65.6	261.0	335	16.76	7.60	24.01	1.49	1" SQ.
70ESN475SD8	118.0	473.0	87.03	348.87	250	16.76	7.60	24.01	1.49	1" SQ.
70ESN700SD8	175.0	700.0	129.07	516.29	170	16.76	7.60	24.01	1.49	1" SQ.
70ESN850SD8	213.0	850.0	157.10	626.93	125	16.76	7.60	24.01	1.49	1" SQ.

Note: 70 Series Tools require a 220/230 power supply to the controller