

H Series 4-120Nm Torque - Pistol Grip - Shut-Off Model - Cleco

Market leading repeatability unmatched accuracy, low maintenance, inertia shut-off, low noise level, efficient 3 chamber air motor, external speed control, oil less blades reversible torque signal port

- Durable, Economical low maintenance



Model Number Nomenclature

120	P	T	H	H	A	XX	Q
Maximum Torque Output 7 - 400 Nm	Tool Configuration P - Pistol S - Inline	Torque Control (-) - Non-Shut-Off T - Air Shut-Off	Torque Delivery H - Hydraulic	Vintage	Air Feed A - Top air feed	Speed 40-4000 RPM	Output Termination Q - Quick-change 2 - 1/4" Sq. Dr. 3 - 3/8" Sq. Dr. 4 - 1/2" Sq. Dr. 6 - 3/4" Sq. Dr.

MODEL	DRIVE TYPE	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT LB	AIR CONSUMPTION		
		MIN FT LB	MAX FT LB	MIN NM	MAX NM			NPT	HOSE I.D.	SCFM
7PTHH352	SQUARE	2.95	2.95	5.2	7	3500	1.74	1/4	3/8	7.06
7PTHH35Q	QUICK CHANGE	2.95	2.95	5.2	7	3500	1.74	1/4	3/8	7.06
7PTHHA352	SQUARE	2.95	2.95	5.2	7	3500	1.94	1/4	3/8	7.06
7PTHHA35Q	QUICK CHANGE	2.95	2.95	5.2	7	3500	1.94	1/4	3/8	7.06
20PTHH403*	SQUARE	14.8	14.8	25.1	34	4000	1.90	1/4	1/2	8.70
20PTHH40Q	QUICK CHANGE	14.8	14.8	25.1	34	4000	1.92	1/4	1/2	8.70
20PTHHA403*	SQUARE	14.8	14.8	25.1	34	4000	2.03	1/4	1/2	8.70
20PTHHA40Q	QUICK CHANGE	14.8	14.8	25.1	34	4000	2.05	1/4	1/2	8.70
35PTHH40Q	QUICK CHANGE	14.8	14.8	25.8	35	4000	2.31	1/4	1/2	15.90
35PTHHA403*	SQUARE	14.8	14.8	25.8	35	4000	2.45	1/4	1/2	15.90
35PTHHA40Q	QUICK CHANGE	14.8	14.8	25.8	35	4000	2.45	1/4	1/2	15.90
55PTHH403*	SQUARE	22.1	22.1	40.6	55	4000	2.54	1/4	1/2	15.90
55PTHHA403*	SQUARE	22.1	22.1	40.6	55	4000	2.67	1/4	1/2	15.90
80PTHH354	SQUARE	36.9	36.9	59	80	3500	3.09	1/4	3/8	19.40
80PTHH35Q	QUICK CHANGE	36.9	36.9	59	80	3500	3.20	1/4	3/8	19.40
80PTHHA354	SQUARE	36.9	36.9	59	80	3500	3.31	1/4	3/8	19.40
80PTHHA35Q	QUICK CHANGE	36.9	36.9	59	80	3500	3.33	1/4	3/8	19.40
110PTHH30Q	QUICK CHANGE	55	55	81	110	3000	3.75	3/8	1/2	19.40
110PTHHA30Q	QUICK CHANGE	55	55	81	110	3000	3.86	3/8	1/2	19.40
11PTHH352*	SQUARE	4.43	4.43	81	110	3500	1.81	1/4	3/8	7.06
11PTHH353*	SQUARE	4.43	4.43	81	110	3500	1.83	1/4	3/8	7.06
11PTHH35Q	QUICK CHANGE	4.43	4.43	81	110	3500	1.87	1/4	3/8	7.06
11PTHHA352*	SQUARE	4.43	4.43	81	110	3500	1.94	1/4	3/8	7.06
11PTHHA353*	SQUARE	4.43	4.43	81	110	3500	1.96	1/4	3/8	7.06
11PTHHA35Q	QUICK CHANGE	4.43	4.43	81	110	3500	2.01	1/4	3/8	7.06
120PTHH304	SQUARE	55	55	89	120	3000	3.75	3/8	1/2	19.40
120PTHHA304	SQUARE	55	55	89	120	3000	3.86	3/8	1/2	19.40

* 7/16" QUICK CHANGE CHUCK AVAILABLE SEPARATELY AS AN ACCESSORY

C Series - High Torque Pistol Grip Non-Shut-off 100-400 nm Torque - Cleco

Durable, Economical low maintenance low noise levels efficient air motor external speed control, oil less blades reversible

- Durable, Economical low maintenance



MODEL	DRIVE TYPE	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT LB	AIR CONSUMPTION		
		MIN FT LB	MAX FT LB	MIN NM	MAX NM			NPT	HOSE I.D.	SCFM
140PH45Q	QUICK CHANGE	74	74	103	140	4500	5.7	3/8	1/2	31.7
160PH456	SQUARE	74	74	118	160	4500	5.7	3/8	1/2	31.7
250PHAF406	SQUARE	118	118	185	250	4000	8.6	3/8	1/2	40.6
400PHF356	SQUARE	185	185	295	400	3500	11.5	3/8	1/2	42.3

C Series 100-160Nm Torque - Pistol Grip - Shut-Off Model - Cleco

Durable, Economical low maintenance low noise levels, external speed control efficient air motor reversible torque signal port

- Durable, Economical low maintenance



MODEL	DRIVE TYPE	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT LB	AIR CONSUMPTION		
		MIN FT LB	MAX FT LB	MIN NM	MAX NM			NPT	HOSE I.D.	SCFM
140PTHC25Q	QUICK CHANGE	74	74	103	140	2500	5.7	3/8	1/2	25.4
160PTHC256	SQUARE	74	74	118	160	2500	5.7	3/8	1/2	25.4

C series 160-250Nm Torque - Pistol Grip - Shut-Off Model - Trigger Throttle - Cleco

Durable, Economical low maintenance low noise levels, external speed control efficient air motor reversible torque signal port

- Durable, Economical low maintenance
- Motor governor equipped
- External torque adjustment
- External speed control
- Reversible
- Oilless blades
- Torque Signal port



MODEL	DRIVE TYPE	TORQUE RANGE				FREE SPEED R/MIN	WEIGHT LB	AIR CONSUMPTION		
		MIN FT LB	MAX FT LB	MIN NM	MAX NM			NPT	HOSE I.D.	SCFM
250PTHC226	SQUARE	118	118	185	250	2200	8.8	3/8	1/2	33.5
400PTHC206	SQUARE	185	185	295	400	2000	11.7	3/8	1/2	33.5