

NeoTek - 30 Series - Corded Electric - Transducer Control - Retractable Spindle (2.6-30 Nm)

- For fixtured applications to ensure bolt engagement
- Configurable LED light rings
- Programmable multi-function buttons
- Brushless Motor
- Transducer Control



MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
30EAR12S131	2.6	12.1	1.9	8.9	1425	3.61	1.64	16.2	0.54	3/8" SQ.
30EAR25S131	5.4	25.0	4.0	18.4	675	4.01	1.82	16.2	0.54	3/8" SQ.
30EAR30S131	7.0	30.0	5.2	22.1	500	4.01	1.82	16.2	0.54	3/8" SQ.

NeoTek - 50 Series - Corded Electric - Transducer Control - Retractable Spindle (8-235 Nm)

- For fixtured applications to ensure bolt engagement
- Configurable LED light rings
- Programmable multi-function buttons
- Brushless Motor
- Transducer Control



MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
50EAR39S231	8.0	39.0	5.9	28.8	1375	5.00	2.20	19.0	0.69	3/8" SQ.
50EAR55S231	12.0	55.0	8.9	40.6	915	5.38	2.37	19.0	0.69	3/8" SQ.
50EAR56S341	11.0	56.0	8.1	41.3	965	5.60	2.51	20.2	0.67	1/2" SQ.
50EAR85S341	17.0	84.0	12.5	62.0	640	5.98	2.68	20.2	0.87	1/2" SQ.
50EAR100S341	20.0	100.0	14.8	73.8	540	6.48	2.91	20.2	0.87	1/2" SQ.
50EAR165S461	33.0	165.0	24.3	121.7	315	7.68	6.81	21.7	1.06	3/4" SQ.
50EAR235S461	49.0	235.0	36.1	173.3	215	8.67	8.46	22.3	1.06	3/4" SQ.