

NeoTek - 30 Series - Corded Electric - Transducer Control - Flush Socket (2.6-30 Nm)

- For low clearance applications
- Configurable LED light rings
- Programmable multi-function buttons
- Brushless Motor
- Transducer Control



MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN
30EFN12F1	2.6	12.1	1.9	8.9	1425	3.61	1.64	16.2	0.54
30EFN25F1	5.4	25.0	4.0	18.4	675	4.01	1.82	16.2	0.54
30EFN30F1	8.0	30.0	5.9	22.1	500	4.01	1.82	16.2	0.54

NeoTek - 50 Series - Corded Electric - Transducer Control - Flush Socket (8-235 Nm)

- For low clearance applications
- Configurable LED light rings
- Programmable multi-function buttons
- Brushless Motor
- Transducer Control



MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN
50EFN39F2	8.0	39.0	5.9	28.8	1375	6.00	2.70	19.0	0.69
50EFN55F2	12.0	55.0	8.9	40.6	915	6.38	2.87	19.0	0.69
50EFN56F3	11.0	56.0	8.1	41.3	965	5.60	2.51	20.2	0.88
50EFN85F3	17.0	84.0	12.5	62.0	640	5.98	2.68	20.2	0.88
50EFN100F3	20.0	100.0	14.8	73.8	540	6.48	2.91	20.2	0.88
50EFN165F4	33.0	165.0	24.3	121.7	315	7.68	3.49	21.7	1.06
50EFN235F4	49.0	235.0	36.1	173.3	215	9.87	4.48	22.3	1.06

NeoTek - 50 Series - Corded Electric - Transducer Control - Tubenut (7.6-40 Nm)

- For fluid line applications
- Configurable LED light rings
- Programmable multi-function buttons
- Brushless Motor
- Transducer Control



MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN
50ETN20T2	7.6	20.0	5.6	14.8	1525	4.13	1.90	18.4
50ETN30T3	11.0	30.0	8.1	22.1	1100	4.23	1.90	18.0
50ETN40T4	14.0	40.0	10.3	29.5	830	5.03	2.20	19.0