

NeoTek - 30 Series - Corded Electric - Transducer Control - Right Angle (1.3-28 Nm)

1 million cycles maintenance free and customizable features to fit any application. Light weight and ergonomic design for applications up to 28 Nm.

- Engineered to provide 1 million cycles maintenance-free
- Repeatability & accuracy of 2.0 Cm/Cmk at +/- 7%
- 1.3 Nm to 28 Nm Torque range
- 3/8 square output drive
- Configurable LED light rings

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	HEAD HEIGHT	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	IN	
30EAN06EA3	1.3	6	.9	4.4	2925	2.5	1.13	14.96	.48	1.42	3/8" SQ.
30EAN12EA3	2.6	12	1.9	8.8	1450	2.5	1.14	14.96	.48	1.42	3/8" SQ.
30EAN21FA3	4.4	21	3.2	15.4	835	2.9	1.32	16.06	.65	1.58	3/8" SQ.
30EAN28FA3	5.7	28	4.2	20.6	615	2.9	1.32	16.06	.65	1.58	3/8" SQ.

NeoTek - 50 Series - Corded Electric - Transducer Control - Right Angle (6-205 Nm)

1 million cycles maintenance free and customizable features to fit any application. High speed and accuracy for applications up to 205 Nm.

- Engineered to provide 1 million cycles maintenance-free
- Repeatability & accuracy of 2.0 Cm/Cmk at +/- 7%
- 6.0 Nm to 205 Nm Torque range
- 3/8, 1/2, 3/4 square output drive
- Configurable LED light rings

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	HEAD HEIGHT	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	IN	
50EAN30FA3	6.0	30	4.4	22.1	1765	3.5	1.60	17.68	.65	1.58	3/8" SQ.
50EAN39GA3	8.0	39	5.9	28.7	1375	3.9	1.77	18.19	.66	1.76	3/8" SQ.
50EAN59HA3	12	59	8.8	43.5	915	4.3	1.94	18.27	.75	2.02	3/8" SQ.
50EAN80JA4	16	80	11.8	59.0	670	4.8	2.17	18.62	.90	1.91	1/2" SQ.
50EAN110KA4	22	109	16.2	80.3	475	6.5	2.76	19.41	1.00	2.37	1/2" SC
50EAN150KB4	32	150	23.6	110.6	320	8.3	3.75	22.01	1.03	2.54	1/2" SQ.
50EAN205NA6	41	205	30.2	151.2	250	8.7	3.93	22.13	1.16	2.44	3/4" SQ.



NeoTek - 70 Series - Corded Electric - Transducer Control - Right Angle (39-350 Nm)



Durability and unsurpassed RPM for high torque applications up to 350 Nm.

- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
70EAN155NA6	39.0	156.0	28.76	115.06	740	14.33	6.50	25.07	1.16	3/4" SQ.
70EAN205NA6	52.0	205.0	38.35	151.20	555	14.33	6.50	25.07	1.16	3/4" SQ.
70EAN240PA6	60.0	239.0	44.25	176.28	480	15.43	7.00	25.78	1.49	3/4" SQ.
70EAN350PA6	88.0	350.0	64.91	258.15	325	15.43	7.00	25.78	1.49	3/4" SQ.

Note: 70 Series Tools require a 220/230 power supply to the controller

NeoTek - 30 Series - Corded Electric - Transducer Control - Inline (0.9-26 Nm)



High speed and accuracy for applications up to 26 Nm. Mounts easily with machined splines and locknut.

- 1 Million Cycles Maintenance Free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- Programmable Multi-function Buttons

MODEL	TORQUE RANGE				FREE SPEED	WEIGHT		LENGTH	SIDE TO CENTER	OUTPUT DRIVE
	MIN NM	MAX NM	MIN FT LB	MAX FT LB	R/MIN	LB	KG	IN	IN	
30ESN05BD2	0.9	4.7	0.66	3.47	4275	2.12	0.96	13.27	0.64	1/4" SQ.
30ESN05BDQ	0.9	4.7	0.66	3.47	4275	2.12	0.96	13.46	0.64	1/4" QC
30ESN12EAQ	3.9	11.6	2.88	8.56	1650	2.34	1.06	14.21	0.64	1/4" QC
30ESN12FA3	3.9	11.6	2.88	8.56	1650	2.34	1.06	14.05	0.64	3/8" SQ.
30ESN19FB3	3.9	19.0	2.88	14.01	1000	2.34	1.06	14.05	0.64	3/8" SQ.
30ESN26FC3	5.1	26.0	3.76	19.18	750	2.34	1.06	14.05	0.64	3/8" SQ.